

Product data sheet

Slimdrive SC

Automatic curved sliding door system for the realization of semi curved solutions and vestibule systems



Product features

Very quiet running, low-wear direct current drive with a height of only 7 cm
40 % more opening width than with linear sliding door drives
Various drive variants possible, e.g. double entrance, corner door, arc, semicircle
Can be networked via CAN bus and integrated into building technology management systems
Independent error recognition and recording
Freely configurable inputs and outputs for different functions
Integrated, rechargeable battery for emergency opening in case of safety-relevant faults, such as power failure
Self-cleaning roller carriage reduces maintenance effort and costs
Various mechanical and electrical lockings are optionally available

Application Areas

Single and double leaf door systems
Interior and exterior doors with high access frequency
Representative building entrances with large incidence of light
Façades with narrow post-rail constructions
Glass façades with the highest design standards
Vestibule systems, in combination with linear sliding doors
Opening widths of 800 to 3000 mm possible
Door leaf weights up to maximally 120 kg
Suitable profile systems are fine-framed profile systems with ISO and mono glass and all-glass systems (GGS)

Product Data Table

Productname	SC
Barrier-free	Yes
Adjustable opening speed (ventilation)	Yes
Adjustable closing speed	Yes
Opening width 2-leaf	800 mm 3000 mm
Clear passage height*	3000 mm
Canopy height (min.)	75 mm
Leaf weight (max.)	100 kg
Leaf weight (max.) 2-leaf	120 kg
Radius (min.)	1000 mm
Moving leaf version	10 mm LSG, Special glass on request
Side elements version	10 mm LSG, 22 mm panel lining, Special glass on request

Surfaces	Powder-coated according to RAL, Anodised light alloy E6/EV1, colour anodised according to sample, coated with polished stainless steel, coated with grit 240 stainless steel, special coating on request
Version of roof structure	optical sheet metal covering, waterproof roof with waterspout, Glass roof
Illumination	with roof variant, not possible with glass roof, according to customer wishes
Floor covering	Scraper mat, Floor mat according to customer wishes
Hot-air curtain system	possible, depends on the ceiling construction
Operation	Display programme switch DPS, Keypad programme switch TPS, PC, Control unit
Approvals	DIN 18650, EN 16005