

Product data sheet

Boxer E

Integrated door closer for single leaf doors with a leaf width of up to 1400 mm with electric hold-open device



Product features

Closing force with variable adjustment of EN2-4 or EN3-6
Can be used for right and left hand doors without conversion
Door closer is embedded in the door leaf and frame and fulfils the highest design demands
Electric hold-open device in the guide rail with hold-open area 80°-120°
Retention force of the hold-open unit is gradually adjustable
Smoke switch control unit can be connected, whose signal makes the door close automatically in the event of a fire
Integrated back check, slows down doors that are thrown open forcefully
Hydraulic latching action which accelerates the door shortly before the closed position
Closing speed can be individually adjusted
All functions can be adjusted in the installed state

Application Areas

Fire and smoke protection doors, proof of suitability for the door required
Right and left single-action doors
Single-action doors up to 1400 mm leaf width, for door weight up to 180 kg
For door leaf thicknesses from 40 mm
Integrated installation
Hold-open systems with integrated hold-open device

Product Data Table

Productname	GEZE Boxer E
-------------	--------------

Accessory

Product name

Set RSZ 6 ECwire
RSZ 6 smoke switch control unit
GEZE GC 152 smoke detector
GEZE GC 153 thermal detector
Surface-mounted box, single
Interruption switch AS 500

Part

Product name

GEZE Boxer 2-4 closer

GEZE Boxer 2-4 2V closer

GEZE Boxer 3-6 closer

E guide rail Boxer