

Product data sheet

TZ 320 S UP

Door control unit for controlling escape route doors with key switch



Product features

- Full-area operable impact cover enables fast and safe activation of the illuminated emergency push button in panic situations
- Coloured supply terminals simplify installation
- 3 freely configurable inputs and 2 freely configurable outputs offer numerous possibilities for additional components
- Number of inputs and outputs can be extended with the KL 220 terminal box
- Integrated key switch enables authorised access to emergency exit

Application Areas

- EItVTR-compliant protection of an emergency exit against unauthorised access
- Networkability via bus enables e.g. interlocking door system control, forwarding of alarms, connection to building management system
- Can be combined with motor locks and swing door drives
- Realisation of a bidirectional emergency exit
- Flush-mounted installation ensures seamless integration into the building

Product Data Table

Productname	TZ 320 S, door control unit, flush mounting
Width	81 mm
Height	152 mm
Operating voltage	24 V DC
Supply voltage	24 V DC
Current consumption	100 mA
Contact rating	30 V / 1 A
Sabotage contact	Yes
Number of inputs	3 Stk.
Number of outputs	2 Stk.
Emergency button	Yes
Visual display	yes
Acoustic signal	75 dB
Temperature range	-10 °C 50 °C
IP rating	IP20
Type of installation	flush-mounting
With ribbon cable	Yes
Parameter setting	ST 220 service terminal
EItVTR	Yes

Accessory

Product name
GEZE IO 420
NOT 220 emergency push button
NOT 220 emergency push button
SCT220
SCT 320 UP, key switch
SCT222
RWS NOTTASTE UP
RWS NOTTASTE UP