

Product data sheet

Slimdrive SLT

Automatic telescopic sliding door system for use in extremely narrow glass façades



Product features

Two parallel-running tracks guide the door leaves and thus achieve high opening widths
Very quiet running, low-wear direct current drive with a height of only 7 cm
Can be networked via CAN bus and integrated into building technology management systems
Independent error recognition and recording
Freely configurable inputs and outputs for different functions
Integrated rechargeable battery for emergency opening and closing in the event of a power failure
Various mechanical and electrical lockings are optionally available

Application Areas

2- and 4-leaf sliding door systems
In confined spaces with small clear opening width or little space next to the door opening
Interior and exterior doors with high access frequency
Opening widths of 1000 to 3600 mm possible
Door leaf weights of up to 80 kg per leaf
Suitable profile systems are fine-framed profile systems with ISO glass and integrated all-glass systems (IGG)

Product Data Table

Productname	SLT
For 2-leaf door systems	Yes
For 4-leaf door systems	Yes
Height	70 mm
Depth	247 mm
Leaf weight (max.) 2-leaf	80 kg
Leaf weight (max.) 4-leaf	70 kg
Opening width 2-leaf	1000 mm 3000 mm
Opening width 4-leaf	1600 mm 3600 mm
Operating temperature	-15 °C 50 °C
Disconnection from mains	Main switch in the drive
Approvals	DIN 18650, EN 16005, DIN EN ISO 13849: Performance Level D

Accessory

Product name

GEZE GC 363
