

Product data sheet

Closer body TS 5000 L



For overhead door closers with guide rail EN 2-6 on the opposite hinge side

AREAS OF APPLICATION

- Fire and smoke protection doors
- Right and left single-action doors
- Single-action doors up to 1400 mm leaf width
- Door leaf installation opposite hinge side and transom installation hinge side

Closer body TS 5000 L



PRODUCT FEATURES

- Closing force can be variably adjusted from the front
- Visual closing force display ensures correct setting
- Closing speed can be adjusted from the front via valve
- Latching action can be adjusted from the front via valve
- Back check can be adjusted from the front via valve
- Door closer, can be used for right and left hand doors
- Minimal installation effort due to low number of individual parts and quick setting

TECHNICAL DATA

Productname	Closer body TS 5000 L
Closing force in accordance with EN 1154	EN 2 - 6
Leaf width (max.)	1400 mm
Type of installation	Door leaf installation opposite hinge side, Transom installation hinge side
Opening angle (max.)	120 °
Identical design for DIN left and DIN right	TRUE
Approvals	Door closer tested in accordance with EN 1154
Suitability for fire protection doors	Yes
Length	287 mm
Width	47 mm
Height	60 mm
Closing force adjustable	Yes, stepless
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Back check integrated	Yes, hydraulically adjustable
Position of closing force adjustment	Front
Visual closing force display	Yes
Safety valve against overload	Yes
Thermo-control valves	Yes

VARIANTS / ORDER INFO

Name	Description	Ident-No.	Colour	Closing force in accordance with EN 1154	Dimensions
TS 5000 L door closer	Closing force EN 2-6, with back check (without guide rail and lever)	029400	white RAL 9016	EN 2 - 6	287 x 47 x 60 mm
TS 5000 L door closer	Closing force EN 2-6, with back check (without guide rail and lever)	137723	stainless steel face plate	EN 2 - 6	287 x 47 x 60 mm
TS 5000 L door closer	Closing force EN 2-6, with back check (without guide rail and lever)	027351	silver-coloured	EN 2 - 6	287 x 47 x 60 mm

Closer body TS 5000 L



Name	Description	Ident-No.	Colour	Closing force in accordance with EN 1154	Dimensions
TS 5000 L door closer	Closing force EN 2-6, with back check (without guide rail and lever)	027352	acc. to RAL	EN 2 - 6	287 x 47 x 60 mm
TS 5000 L door closer	Closing force EN 2-6, with back check (without guide rail and lever)	119579	black RAL 9005	EN 2 - 6	287 x 47 x 60 mm