

Product data sheet

TS 5000 ISM

Overhead door closer system with guide rail for double leaf doors with closing sequence control



Product features

System comprising two door closers TS 5000 and an ISM guide rail
Closing force of EN2-6 with variable adjustment
Can be used for right and left hand doors without conversion
Closing sequence control holds the active leaf in the waiting position until the passive leaf is closed
Hydraulic latching action which accelerates the door shortly before the closed position
Closing speed can be individually adjusted
Integrated back check, slows down doors that are thrown open forcefully
Visual closing force display for easy control of the setting
All functions can be adjusted from the front

Application Areas

Double-leaf single-action doors
Symmetrical and asymmetrical door division possible
Single-action doors up to 2800 mm hinge clearance and 1400 mm leaf width, overlength up to 3200 mm
Minimum hinge clearance 1300 mm, minimum width of passive leaf 400 mm
Door leaf installation hinge side

Product Data Table

Productname	GEZE TS 5000 ISM
Suitability for fire protection doors	Yes

Accessory

Product name
GEZE CB flex
GEZE magnetic counter plate for GEZE hold-open magnets
GEZE magnetic counter plate for GEZE hold-open magnets
GEZE magnetic counter plate for GEZE hold-open magnets
GEZE door hold-open magnet, 24 V DC - 490 N retention force, approved for use with all GEZE smoke switch control units
GEZE door hold-open magnet, 24 V DC - 490 N retention force, approved for use with all GEZE smoke switch control units
GEZE door hold-open magnet, 24 V DC - 490 N retention force, approved for use with all GEZE smoke switch control units
GEZE door hold-open magnet, 24 V DC - 490 N retention force, approved for use with all GEZE smoke switch control units

Product name

GEZE door hold-open magnet, 24 V DC - 490 N retention force, approved for use with all GEZE smoke switch control units

GEZE door hold-open magnet, 24 V DC - 490 N retention force, approved for use with all GEZE smoke switch control units

GEZE door hold-open magnet, 24 V DC - 490 N retention force, approved for use with all GEZE smoke switch control units

Mechanical hold-open unit

Set RSZ 6 ECwire

Cover cap door closer

RSZ 6 smoke switch control unit

GEZE Rauchschalter GC 152

GEZE GC 153 thermal detector

Surface-mounted box, single

Interruption switch AS 500

Part

Product name

ISM guide rail TS 5000

ISM guide rail TS 5000 extra length

GEZE TS 5000 closer

GEZE TS 5000 S closer