

Product data sheet

TZ 320 S AP

Door control unit for controlling escape route doors with key switch



Product features

- Full-area operable impact cover enables fast and safe activation of the illuminated emergency button in panic situations
- Coloured supply terminals simplify installation
- 3 freely configurable inputs and 2 freely configurable outputs offer numerous possibilities for additional components
- Number of inputs and outputs can be extended with the KL 220 terminal box
- Integrated key switch enables authorised access to emergency exit

Application Areas

- EItVTR-compliant protection of an emergency exit against unauthorised access
- Can be used on single and double leaf doors
- Connectivity via bus enables e.g. interlocking door system control, forwarding of alarms, connection to building management system
- Can be combined with motor locks and swing door drives
- Realisation of a bidirectional emergency exit
- Surface mounting allows subsequent installation on the door with little effort

Product Data Table

Product features	Door control unit TZ 320 S, surface mounting
Width	77 mm
Height	197 mm
Installation depth	88 mm
Operating voltage	24 V DC
Supply voltage	24 V DC
Current consumption	100 mA
Contact rating	30 V / 1 A
Sabotage contact	Yes
Number of inputs	3 Stk.
Number of outputs	2 Stk.
Emergency button	Yes
Visual display	yes
Acoustic signal	75 dB
Temperature range	-10 °C - 50 °C
IP rating	IP30
Type of installation	surface-mounting
With ribbon cable	Yes
Parameter setting	ST 220 service terminal
EItVTR	Yes

Accessory

Product name
GEZE IO 420
Emergency stop switch NOT 220
Emergency stop switch NOT 220
SCT220
SCT 320 flush mounting, key switch
SCT222
RWS NOTTASTE UP
RWS NOTTASTE UP