

# Product data sheet Perlan 140 glass with 30 mm glass clamping plate ceiling installation



Sliding door fitting system for glass doors with a leaf weight of 80 kg and ceiling installation

#### **AREAS OF APPLICATION**

- ightarrow Frequently used interior sliding doors
- ightarrow Living, office, and conference areas as well as hotels
- ightarrow Installation of fittings in all visible areas
- ightarrow Single and multiple-leaf sliding doors
- ightarrow Installation to the ceiling



#### **PRODUCT FEATURES**

- ightarrow Sliding door fitting for leaf weights up to 80 kg
- ightarrow For glass leaves with a 30 mm glass clamping plate
- $\rightarrow$  With damping on one or both sides for doors with up to 80 kg leaf weight, so that the door is quietly slowed down and moved into the end position
- ightarrow Adjustable height compensation levels out unevenness between the ceiling and the track
- ightarrow Precision ball bearings in the roller carriages offer very smooth sliding action
- ightarrow Tested for durability in accordance with DIN EN 1527 over 100,000 test cycles

#### **TECHNICAL DATA**

Productname

Perlan 140 glass with 30 mm glass clamping plate ceiling installation

#### PART

#### **PERLAN 140 SET FOR TIMBER LEAVES**

Sliding door fitting for glass leaves with up to 140 kg leaf weight



Designation	Description	ldent- No.	Colour	Leaf width (min.)	Leaf width (max.)
Perlan 140 set for timber leaves	For ceiling installation with standard suspension plate, up to 140 kg leaf weight	119354	EV1	500 mm	1040 mm
Perlan 140 set for timber leaves	For ceiling installation with standard suspension plate, up to 140 kg leaf weight	119355	EV1	500 mm	1240 mm
Perlan 140 set for timber leaves	For ceiling installation with standard suspension plate, up to 140 kg leaf weight	119353	EV1	500 mm	840 mm
Perlan 140 set for timber leaves	For ceiling installation with standard suspension plate, up to 140 kg leaf weight	119356	EV1	500 mm	1440 mm
Perlan 140 set for timber leaves	For ceiling installation with standard suspension plate, up to 140 kg leaf weight	119357	EV1	500 mm	1640 mm

### Product data sheet | Page 3 of 9 Perlan 140 glass with 30 mm glass clamping plate ceiling installation

TRACK PERLAN 140

Track for sliding door fitting

Designation	Description	Ident-No.	Colour
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	142518	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	128660	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	128662	Stainless steel optic
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135061	Stainless steel optic
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135048	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135050	Stainless steel optic
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135049	Stainless steel optic
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135047	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	142519	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135046	EV1

#### FLOOR GUIDE FOR GLASS LEAF

Floor guide with variable adjustment for glass thicknesses 8, 10 and 12  $\,\rm mm$ 

Designation	Description	ldent- No.	Colour	Glass thickness
Floor guide for glass leaf (adjustable)	with variable adjustment for glass thickness 8-13.5 mm, with frieze band for noise reduction with structured glass surfaces, without attachment material	120417	silver- coloured	8 - 13.5 mm

#### SET CAPS FOR GLASS CLAMPING PLATE 30 MM \*

End cap for glass clamping plate 30, set comprising 2 pieces







### Perlan 140 glass with 30 mm glass clamping plate ceiling installation



### GLASS CLAMPING PLATE 30 MM SET, CONTINUOUSLY BLENDED

Glass clamping plate 30 for leaf weights up to 80 kg with continuous cover panels



Designation	Description	ldent- No.	Glass thickness
Glass clamping plate 30 mm set, continuously blended	Consisting of 2 glass clamping plates incl. suspension bolts, continuous bespoke cover and end caps, EV1 or stainless steel optic, up to 80 kg leaf weight, for 8–12 mm toughened safety glass	142368	8 – 12 mm

#### **GLASS CLAMPING PLATE 30 MM SET, WITH COVERING**

Glass clamping plate 30 mm including cover for leaf weights up to 80 kg



### Perlan 140 glass with 30 mm glass clamping plate ceiling installation

#### **GLASS CLAMPING PLATE 30 MM SET, WITHOUT COVER**

Glass clamping plate 30 for leaf weights up to 80 kg without cover

Description

set, without cover

Designation

### ACCESSORIES

Glass clamping plate 30 mm

#### END STOP WITH ADJUSTABLE HOLD-OPEN SPRING

Adjustable end stop for Perlan sliding door fitting

Designation	Ident-No.
End stop with adjustable hold-open spring	069274

Consisting of 2 glass clamping plates incl. suspension bolts, up to 80 kg leaf weight, for 8–12 mm toughened safety glass

#### **HOLD-OPEN SPRING**

Hold-open spring for Perlan 140 end stop

Designation	Ident-No.
Hold-open spring	064242



No.

142364







thickness

8 - 12 mm



## **DOOR STOP** End stop for sliding leaves

Designation	Ident-No.
Door stop	000339
Door stop	000342

### LSG GLASS / METAL GLUE \*

Glass metal glueing kit for connecting aluminium brackets with glass panes

Designation	Description	Ident-No.
LSG glass / metal glue 50 g *	for up to 30 sliding panels	133039

#### CLAMPING INSERT, GLASS CLAMPING PLATE 30 MM \*

Clamping shim for glass thicknesses of 12.76 mm (1/2 inch)

Designation	Description	Ident-No.
Clamping insert, glass clamping plate 30 mm	for 2 glass clamping plates, for use with 12.7 mm (1/2 inch) toughened safety glass	142634

#### **HEIGHT COMPENSATION MECHANISM / CEILING DISTANCE** SET, WITH VARIABLE ADJUSTMENT

Height compensation with variable adjustment for ceiling installation of tracks

### Product data sheet | Page 6 of 9

# Perlan 140 glass with 30 mm glass clamping plate ceiling installation

-	











Designation	Description	ldent- No.
Height compensation mechanism / ceiling distance set, with variable adjustment	6 pieces, height compensation mechanism with variable adjustment from 13 mm to 18 mm. For use for ceiling mounting using clip-on cover 100/145 as well as for general use on uneven ceilings	138099

### PERLAN SOFTSTOP SET, MEDIUM VERSION, DAMPED ON ONE SIDE, UP TO 80 KG

Perlan SoftStop damping on one side for leaf weights up to 80 kg and leaf widths of 900 up to 1290 mm

-

1

(.).

Designation	Description	ldent- No.	Leaf width (min.)	Leaf width (max.)
Perlan SoftStop set, medium, one side	The set includes: 2 x roller carriage with damping unit on one side, 2 x end stop, 1 x trigger with fixing screw, 2 x standard suspension plate	128877	900 mm	1290 mm

### PERLAN SOFTSTOP SET, LONG VERSION, DAMPED ON BOTH SIDES, UP TO 80 KG

Perlan SoftStop damping on both sides for leaf weights up to 80 kg

Designation	Description	ldent- No.	Leaf width (min.)	Leaf width (max.)
Perlan SoftStop set, long, both sides	The set includes: 2 x roller carriage with damping unit on both sides, 2 x end stop, 2 x trigger with fixing screws, 2 x standard suspension plate	128891	1290 mm	1700 mm

#### SET PERLAN SOFTSTOPDUO, DAMPED ON BOTH SIDES

Perlan SoftStopDuo with damping on both sides up to 80 kg leaf weight

### Perlan 140 glass with 30 mm glass clamping plate ceiling installation

Designation	Description	ldent- No.	Leaf width (min.)	Leaf width (max.)
Perlan SoftStopDuo set, damped on both sides, up to 80 kg	The set includes: 2 x roller carriage with damping unit on both sides, 2 x end stop, 2 x trigger with fixing screws, 2 x standard suspension plate	150071	750 mm	1290 mm

#### LSG GLUEING BRACKET SET \*

Aluminium glueing bracket for LSG and glass clamping plate 30



#### **DOOR PULL HANDLE, CONFIGURED \***

Push bar - round design for installation on glass leaves

Designation	Ident-No.	Colour
Door pull handle, configured *	127616	Stainless steel

#### PERLAN SOFTSTOP SET, SHORT VERSION, DAMPED ON ONE SIDE, UP TO 80 KG

Perlan SoftStop damping on one side for leaf weights up to 80 kg and leaf widths of 575 to 900 mm

001

Designation	Description	ldent- No.	Leaf width (min.)	Leaf width (max.)
Perlan SoftStop set, short, one side	The set includes: 2 x roller carriage with damping unit on one side, 2 x end stop, 1 x trigger with fixing screw, 2 x standard suspension plate	128876	575 mm	900 mm







#### **COMPLETE CLIP-ON COVER SET 100**

Clip-on cover for covering Perlan door fitting systems



Designation	Description	Ident-No.	Type of installation
Complete clip-on cover set 100	for wall and ceiling mounting, continuous cover, bespoke configuration	138098	Wall, Ceiling

\* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.